



Cartridge Filter Housing

115 Design

The 115 design is a leg mounted, free standing housing with split shell design.

The housing is available with multiple amount of cartridges up to 40" of length. The center positioned, split shell opening style is equipped with a Cast Vee clamp as standard for pressures ranging from FV - 10 bar. Leg mounted with the split shell opening, this is the ideal choice when using Single Open End plug in style cartridges. The simple to lift off lightweight dome allows full and easy access to the cartridges for rapid change-outs.

With the free draining clean chamber, the 115 design housings suit processes where cleanliness and ease of operation are essential. Accepting both standard Double Open End and Single Open End cartridges, this leg mounted, free standing housing will suit most applications.

The 115 design will accept the full range of IFAB and industry standard cartridges with nominal lengths of 20, 30 and 40".

Key Product Features

- Split body design allows easy access to cartridges on change-out
- Dished bottom end allows complete drainage of clean chamber, leading to improved system cleanliness
- Adjustable strap legs allow the user to set inlet and outlet heights
- Vee clamp closures use unique 'W' style seal for reliable leak free operation
- High quality cast Vee clamps for safety and security
- Cast compression nut with integral PTFE washer for easy, hand tight cartridge sealing
- PED and ATEX Compliant
- WRAS Approved product



Suitable for a wide range of processes



316L St. Steel



7-10 Bar



150°C



See webpage for related products



Custom made & OEM available



Designed by **IFAB** Sweden



CE PED 97/23/EC

Skandinaviska **IFAB** Filtrering AB

Hangarvägen 9

SE-42337 Torslanda, Sweden

Phone:

+46 31 92 20 70

Fax:

+46 31 92 23 32

E-mail:

info@ifab.se

Web:

www.ifab.se